



Environmental simulation chambers

MK | MKF | MKT | MKFT



Technical data at a glance



| | MK 53 | MK 115 | MKF 115 | MKT 115 | MK 240 | MKF 240 | MKT 240 | MKFT 240 | MK 720 | MKF 720 | MKT 720 |
|---|------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|
| Exterior dimensions (mm) | | | | | | | | | | | |
| Width | 745 | 1000 | 1000 | 1000 | 1135 | 1135 | 1135 | 1135 | 1615 | 1615 | 1615 |
| Height (incl. feet/castors) | 1245 | 1725 | 1725 | 1725 | 1725 | 1725 | 1940 | 1940 | 2005 | 2005 | 2005 |
| Depth (excl. 50 mm for door handle) | 795 | 915 | 915 | 915 | 1000 | 1000 | 1000 | 1000 | 1230 | 1230 | 1230 |
| Interior dimensions (mm) | | | | | | | | | | | |
| Width | 402 | 600 | 600 | 600 | 735 | 735 | 735 | 735 | 1200 | 1200 | 1200 |
| Height | 402 | 480 | 480 | 480 | 700 | 700 | 700 | 700 | 1020 | 1020 | 1020 |
| Depth | 330 | 400 | 400 | 400 | 443 | 443 | 443 | 443 | 600 | 600 | 600 |
| Interior volume (l) | 53 | 115 | 115 | 115 | 228 | 228 | 228 | 228 | 734 | 734 | 734 |
| Weight (empty) kg | 150 | 260 | 280 | 300 | 340 | 360 | 380 | 400 | 590 | 590 | 610 |
| Temperature data | | | | | | | | | | | |
| Temperature range (°C) | -40 – 180 | -40 – 180 | -40 – 180 | -70 – 180 | -40 – 180 | -40 – 180 | -70 – 180 | -70 – 180 | -40 – 180 | -40 – 180 | -70 – 180 |
| Temperature fluctuation (± K) | 0,3 | 0,1 – 0,5 | 0,1 – 0,6 | 0,1 – 0,6 | 0,1 – 0,5 | 0,1 – 0,5 | 0,1 – 0,4 | 0,1 – 0,5 | 0,1 – 0,5 | 0,1 – 0,5 | 0,1 – 0,5 |
| Temperature uniformity ± K) | 2,0 | 0,1 – 2,0 | 0,1 – 1,3 | 0,2 – 1,8 | 0,1 – 1,2 | 0,1 – 1,5 | 0,1 – 1,0 | 0,2 – 1,8 | 0,3 – 2,0 | 0,1 – 1,8 | 0,3 – 2,0 |
| Average heating rate acc. IEC 60068-3-5 (K/min) | 4,6 | 5,3 | 5,5 | 5,3 | 5 | 5 | 5 | 5 | 4 | 4,8 | 4,5 |
| Average cooling rate acc. IEC 60068-3-5 (K/min) | 4,1 | 5,0 | 4,5 | 4,2 | 4,5 | 5 | 4,2 | 4,2 | 4,5 | 4,8 | 4,2 |
| Heat Compensation, max. (W) | 500 | 2000 | 2500 | 1800 | 2000 | 2800 | 3000 | 3000 | 6500 | 6500 | 5500 |
| Climatical data | | | | | | | | | | | |
| Temperature range (°C) | – | – | 10 – 95 | – | – | 10 – 95 | – | 10 – 95 | – | 10 – 95 | – |
| Humidity area (% RH) | – | – | 10 – 98 | – | – | 10 – 98 | – | 10 – 98 | – | 10 – 98 | – |
| Temperature fluctuation (± K) | – | – | 0,1 – 1,3 | – | – | 0,1 – 1,3 | – | 0,1 – 1,5 | – | 0,2 – 1,5 | – |
| Heat Compensation, max. (W) | – | – | 400 | – | – | 400 | – | 400 | – | 1000 | – |
| Electrical data | | | | | | | | | | | |
| Nominal voltage (±10 %) 50 Hz (V) | 230 1N~ | 400 3N~ | 400 3N~ | 400 3N~ | 400 3N~ | 400 3N~ | 400 3N~ | 400 3N~ | 400 3N~ | 400 3N~ | 400 3N~ |
| Nominal power (kW) | 2,6 | 3,5 | 4,2 | 5,5 | 4,2 | 6,8 | 6,5 | 7,5 | 7,2 | 11 | 13 |
| Noise Level (ca. dB(A)) | 59 | 62 | 62 | 64 | 62 | 65 | 64 | 65 | 64 | 65 | 65 |
| Order number | 9020-0006 | 9020-0175 | 9020-0107 | 9020-0151 | 9020-0181 | 9020-0132 | 9020-0196 | 9020-0080 | 9020-0197 | 9020-0198 | 9020-0082 |

7002-0135 | 08-2011 | Information and technical data contained in this flyer are subject to alteration.

BINDER GmbH
Im Mittleren Ösch 5
78532 Tuttlingen
Germany

BINDER Inc.
Bohemia, NY | USA
www.binder-world.us

BINDER Russia & CIS
Moskow | Russia
www.binder-world.ru

BINDER Asia Pacific Ltd
Kwun Tong Kowloon,
Hong Kong | China

Shanghai Office
Shanghai | China

www.binder-world.com

Perfectly matched to testing standards. Optimally designed for reliability.

We were the first to realize that climate chambers nowadays have to do so much more than just testing. They are part of a process in which absolute reliability is paramount. Climate chambers from BINDER for industrial use are perfectly matched to the standards or individual requirements of quality assurance and development.

MK | MKF | MKT | MKFT series

The basis for reliable materials testing

Whether EN, IEC, MIL standards or an individual specification – with a BINDER environmental simulation chamber, you also have complex alternating climate profiles safely under control. The vapor pressure humidification system and our patented APT.line™ airflow design ensure perfect test conditions. This guarantees exact measurements over the entire temperature range of -70 °C und $+180\text{ °C}$ at a temperature dynamic of 5K per minute. The ideal basis for reliable materials testing and the success of your work.



Automotive industry



Electronics testing



Air and space travel



Materials testing

MK | MKF | MKT | MKFT series

A number of advantages standard:



Reliable test results



Convenient work environment



Absolute control



Maximum flexibility



- ▶ APT.line™ for homogeneous climate conditions even under a full load
- ▶ Same test conditions throughout the chamber interior
- ▶ Fast response times thanks to vapor pressure humidification
- ▶ Drift-free, capacitive humidity sensor for accurate measured values

- ▶ Large access area for convenient assembly
- ▶ Convenient operation thanks to controls accessible from the front
- ▶ Minimal maintenance requirements thanks to capacitive humidity sensor
- ▶ Optimum use of space

- ▶ Continuous logging thanks to years of proven validation and documentation materials
- ▶ Standard viewing window allows visual control without interrupting the test procedure

- ▶ Rugged chassis with rollers from 115 l
- ▶ Water supply independent of location
- ▶ Sewage pump for discharges up to 1 m in height
- ▶ Generous standard equipment



MK series— for cyclic temperature testing

The smart alternative to expensive individual solutions for cyclic temperature testing: The MK series masters all heating and cooling testing between $-40\text{ }^{\circ}\text{C}$ and $180\text{ }^{\circ}\text{C}$. It distinguishes itself through precision and performance. The APT.line™ pre-heating chamber technology ensures natural simulation – and thus reliable test results.

► STANDARD EQUIPMENT

- Electronically controlled APT.line™ preheating chamber technology
- MCS controller with 25 storable programs of 100 sections each for a maximum of 500 program segments
- User friendly LCD screen
- Easy-to-read menu guide
- Integrated electronic chart recorder
- Variety of options for the graphic display of process parameters
- Real time
- Programmable condensation protection for test material
- 230 V power socket on the right-side operating panel (except MK 53)
- Adjustable ramp function via program editor
- Access port \varnothing 80 mm top (MK 53), \varnothing 50 mm, left side (MK 115, 240),
- 2 access ports \varnothing 80 mm right and left side (MK 720)
- Temperature safety device class 2 (DIN 12880) with visual and acoustic temperature alarm
- Heated viewing window with LED interior lighting
- Ethernet or RS 422 interface for GLP/GMP and FDA guideline 21 CFR Part 11 compliant APT-COM™ DataControlSystem software
- 4 castors (2 with brakes)
- Stainless steel rack included
- BINDER test confirmation



► OPTIONS / ACCESSORIES



- **Notch-type access port in door** provides easy connection of measuring instruments to test specimens



- **Reinforced shelf** to ensure safe and stable storage of heavy test specimens



- **BINDER INDIVIDUAL** MK with manual access openings, which is convenient when working with test specimens without disturbing the climatic conditions



MKF series – for complex alternating climate profiles

Ideally suited for all testing based on current temperature and climate testing standards: The MKF series meets the requirements based on EN, IEC, MIL standards and several tests derived from these standards. The required temperature and humidity values are quickly achieved and accurately maintained thanks to high dynamics. This guarantees exact measurement results at any time.

► STANDARD EQUIPMENT

- Electronically controlled APT.line™ preheating chamber technology
- MCS controller with 25 storable programs of 100 sections each for a maximum of 500 program segments
 - User friendly LCD screen
 - Easy-to-read menu guide
 - Integrated electronic chart recorder
 - Variety of options for the graphic display of process parameters
 - Real time
- Electronically controlled humidification and dehumidification system with capacitive humidity sensor and pressurized steam
- Integrated water storage tank
- Heated viewing window with interior illumination
- Programable condensation protection for test material
- Adjustable ramp functions via program editor
- 230 V power socket on the right-side operating panel
- Temperature safety device, Class 2 (DIN 12880) with visual and acoustic temperature alarm
- 4 potential-free relay outputs that can be activated via MCS controller
- Ethernet interface for use with APT-COM™ DataControlSystem software
- 1 access port Ø 50 mm , left side
- 4 castors (2 with brakes)
- Stainless steel rack include
- BINDER test confirmation



► OPTIONS / ACCESSORIES



- **Notch-type access port in door**
provides easy connection of measuring instruments to test specimens



- **Various access ports with silicone plug** for introducing external measuring instruments into the chamber



- **BINDER PURE AQUA Service**
Flexible water treatment system extends maintenance intervals



- **BINDER INDIVIDUAL**
MKF with a larger viewing window

MKT series – for complex temperature profiles

The specialists for extreme testing: The MKT meets all requirements for complex test cycles between $-70\text{ }^{\circ}\text{C}$ and $180\text{ }^{\circ}\text{C}$. Their advantages include fast heating and cooling, as well as homogeneous airflow. The chamber interior offers perfect test conditions – even under a full load.

► STANDARD EQUIPMENT

- Electronically controlled APT.line™ preheating chamber technology
- MCS controller with 25 storable programs of 100 sections each for a maximum of 500 program segments
 - User friendly LCD screen
 - Easy-to-read menu guide
 - Integrated electronic chart recorder
 - Variety of options for the graphic display of process parameters
 - Real time
- Programmable condensation protection for test material
- 230 V power socket on the right-side operating panel (except MK 53)
- Adjustable ramp function via program editor
- Access port $\varnothing 50\text{ mm}$, left side
- Temperature safety device class 2 (DIN 12880) with visual and acoustic temperature alarm
- Heated viewing window with LED interior lighting
- Ethernet or RS 422 interface for GLP/GMP and FDA guideline 21 CFR Part 11 compliant APT-COM™ DataControlSystem software
- 4 castors (2 with brakes)
- Stainless steel rack included
- BINDER test confirmation



► OPTIONS / ACCESSORIES



- **Notch-type access port in door** provides easy connection of measuring instruments to test specimens



- **Reinforced shelf** to ensure safe and stable storage of heavy test specimens



- **BINDER INDIVIDUAL** MKT with various access ports for multiple instrument connection leads



MKFT series – for dynamic temperature profiles

The specialists for extreme testing: The MKT meets all requirements for complex test cycles between $-70\text{ }^{\circ}\text{C}$ and $180\text{ }^{\circ}\text{C}$. Their advantages include fast heating and cooling, as well as homogeneous airflow. The chamber interior offers perfect test conditions – even under a full load.

► STANDARD EQUIPMENT

- Electronically controlled APT.line™ preheating chamber technology
- MCS controller with 25 storable programs of 100 sections each for a maximum of 500 program segments
 - ▶ User friendly LCD screen
 - ▶ Easy-to-read menu guide
 - ▶ Integrated electronic chart recorder
 - ▶ Variety of options for the graphic display of process parameters
 - ▶ Real time
- Programmable condensation protection for test material
- 230 V power socket on the right-side operating panel (except MK 53)
- Adjustable ramp function via program editor
- Access port $\varnothing 50\text{ mm}$, left side
- Temperature safety device class 2 (DIN 12880) with visual and acoustic temperature alarm
- Heated viewing window with LED interior lighting
- Ethernet or RS 422 interface for GLP/GMP and FDA guideline 21 CFR Part 11 compliant APT-COM™ DataControlSystem software
- 4 castors (2 with brakes)
- Stainless steel rack included
- BINDER test confirmation



► OPTIONS / ACCESSORIES



- **BINDER PURE AQUA Service**
Flexible water treatment system extends maintenance intervals



- **BINDER Data Logger kit**
for independent recording of temperature and humidity data



- **BINDER INDIVIDUAL**
MKF with reinforced inner chamber and solidly mounted perforated shelves for very heavy test specimens